

Features

- The support feet are set back on the division panel, connected to the front framework to maintain conformity to NBS K32/112A panel cubicles fully framed
- Designed to cope with all reasonable falls in floor level
- Available with anti-finger and anti-nip detail.
- Concealed fixings
- The sprung nylon hinges are adjustable to open in or out
- Breakout strip for emergency cubicle entry
- Available as an elevated system













K32/112A

Manufacturer: Prospec Limited, Canklow Meadows Estate, West Bawtry Road,

Rotherham, S60 2XL, Tel: 01709 377147, Fax: 01709 375239, Web: www.prospec.co.uk E-mail: sales@prospec.co.uk

Product reference: Conform

Overall Cubicle Height: 2006mm including floor clearance of 150mm.

Frame & Finish: Aluminium extrusions satin silver anodised to 25 microns.

Fittings: Extruded satin anodised aluminium headrail and profiles; adjustable anodised aluminium support legs / floor attachments with fully concealed stainless steel fixings and nylon foot cover, set back 200mm from the front face on the division panels.

Door Fittings: 3N° solid colour nylon covered heavy-duty stainless steel / brass hinges per door; concealed nylon door latch; standard handle assembly; emergency breakout strip; DDA compliant handle set with lever action turn and horizontal grab handles; 1 coat hook per cubicle and 2 coat hooks to DDA compliant cubicles.

Pilasters, Doors & End Panels: 12mm compact grade laminate.

Partition Panels: 12mm compact grade laminate.

Edge Treatment: Bull-nosed with radiused corners.

Colour/Finish: Select from manufacturer's range availability.

Accessories: Option of anodised aluminium door furniture; anti-peep rails; anti-camera skirting; door holder for outward opening doors; door closers.

Also available in suspended version with load bearing head beam designed for high-use.

